



ABRASION/MECHANICAL

ROUNDIT® 2000 NX Red

Product Highlights

- Operating temperature from -60°C to 200°C (-76°F to 392°F)
- ASD EN 6049-006
- Excellent cut-through and abrasion resistance
- Self-wrapping design
- Ideal for reworking components without disconnecting them
- Lightweight construction
- Tracer indicating the maximum operating diameter
- Oil and water repellent



ROUNDIT® 2000 NX is a self-wrapping sleeve manufactured from PPS monofilaments and Nomex* with an oil and water repellent treatment, designed for mechanical protection and maintenance of wire and cable bundles. Its construction with 100% covering ratio provides excellent cut-through and abrasion resistance.

ROUNDIT 2000 NX in red is designed to identify wire harnesses connected with weapon systems.

The self-wrapping feature allows for quick and easy installation and removal of the product for assembly and maintenance. ROUNDIT 2000 NX Red also accommodates breakouts.

This design offers innovative solutions to the protection of breakout areas and also provides ease of removal when inspection or maintenance of cables is necessary.

ROUNDIT 2000 NX has many applications in the aeronautical and military industries.

*Nomex is a registered trademark of "E. I. DuPont de Nemours".



As an added benefit, the patented ROUNDIT® Tool will help improve installation time and is designed to install ROUNDIT® products on cable and wire configurations.



Our manufacturing sites are certified ISO 9000, QS 9000 or ISO/TS 16949 and ISO 14001

E_RI2000NXR_05122009

BentleyHarris®
Protection Products